

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

 Product Name: The Exterior Series: .005 Advantage

 Product Synonym(s):

 Impact Acrylic

 Chemical Family:

 Acrylic Copolymer

 Chemical Formula:

 Mixture

 Chemical Name:

 Mixture

 EPA Reg Number:

 Product Use:

 Interior/Exterior Signage, Personal Identification, Other

 Manufactured By:

 P.O. Box 7065

 Algonquin, IL 60142, USA

Telephone Numbers	Available Hours	Phone Number
IPI Customer Service	8:30am-4:30pm CST	1-815-477-0778

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient Name	CAS Registry Number	Typical Wt. %	<u>OSHA</u>
P (EA/MMA)	Proprietary	50-54	Ν
Acrylic Styrene Copolymer	Proprietary	35-50	Ν
Ethyl acrylate	140-88-5	< 0.1	Y
Methyl methacrylate	80-62-6	< 0.5	Y

The ingredient(s) marked with a "Y" in the OSHA column are recognized as hazardous chemicals according to the criteria of the OSHA Hazardous Communication Standard (29 CFR 1910.1200).

While this material is not classified as hazardous under Federal OSHA regulations, this MSDS contains valuable information critical to the proper handling and correct use of this product. This MSDS should be retained and accessible for employees and other users of this product.

The ingredients of this product are all on the TSCA Inventory list.

3. HAZARDS INDENTIFICATION

EMERGENCY OVERVIEW:

Sheet material, various sizes, and mild odor. CAUTION! MELT PROCESSING RELEASES VAPORS WHICH MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION

POTENTIAL HEALTH EFECTS:

Skin contact and inhalation of dust are expected to be the primary routes of occupational exposure to this material. Due to its chemical and physical properties, this material does not require special handling other than the good industrial hygiene and safety practices employed with any industrial material of this type.

Ethyl acrylate is listed as a substance that may reasonably be anticipated to be a carcinogen by the National Toxicology Program (NTP) and is classified as "possibly carcinogenic to humans" by the International Agency for Research on Cancer.

4. FIRST AID MEASURES

IF IN EYES:

Flush eyes with plenty of water; remove contact lenses after the first 1-2 minutes then continue flushing for several minutes. Only mechanical effects expected. Get medical attention if irritation persists.

IN CASE OF CONTACT:

If molten material comes in contact with the skin, do not apply ice but cool under running stream of water. DO NOT attempt to remove the material from the skin. Removal could result in severe damage. Wash clothing before reuse. Get medical attention if irritation develops and persists.

5. FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES:Auto-Ignition Temperature39

Auto-Ignition Temperature 393 C/739 F Flash Point – NA Flash Point Method Flammable Limits: Upper – NA Lower –NA

EXTINGUISHING MEDIA:

Water fog or spray, foam, dry chemical or carbon dioxide.

FIRE FIGHTING INSTRUCTIONS:

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand NIOSH approved or equivalent). Fire fighting equipment should be thoroughly decontaminated after use.

FIRE AND EXPLOSION HAZARDS:

Heated material can form flammable vapors with air.

6. ACCIDENTAL RELEASE MEASURES

IN CASE OF SPILL OR LEAK:

Contain spill. Sweep or scoop up and remove to suitable container. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

7. HANDLING AND STORAGE

HANDLING:

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container closed. Use only with adequate ventilation.

STORAGE:

Avoid temperature extremes during storage; ambient temperature preferred.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS:

Adequate ventilation in work area is needed due to dust or vapors created during fabrication.

PERSONAL PROTECTIVE EQUIPMENT (PPE):

EYE/FACE PROTECTION:

Safety glasses or face shield should be used. If exposed to dust, chemical glasses may be required. <u>SKIN PROTECTION:</u> No precautions other than clean body-covering clothing should be needed. Use insulated gloves for thermal protection, when desired. <u>RESPIRATORY PROTECTION:</u>

In dusty atmospheres, use an approved respirator.



Date: 5/9/2012

MATERIAL SAFETY DATA SHEETS

9. PHYSICAL AND CHEMICAL PROPERTIES

<u>APPEARANCE/ODOR:</u> Various colors, characteristic odor

BOILING POINT: N/A

VAPOR PRESSURE: N/A

VAPOR DENSITY: N/A

SPECIFIC GRAVITY: 1.15-1.19

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable

CONDITIONS TO AVOID:

Prolonged contact with acids, alkalis and strong oxidizing agents may attack or dissolve the polymer.

11. TOXICOLOGY INFORMATION

No data available

12. ECOLOGICAL INFORMATION

MOVEMENT & PARTITIONING:

In the terrestrial environment, material is expected to remain in the soil. In the aquatic environment, material will sink and remain in the sediment.

DEGRADATION & PERSISTENCE:

This water insoluble polymeric solid is expected to be inert in the environment. Surface photo degradation is expected with exposure to sunlight. No appreciable biodegradation is expected.

ECOTOXICITY:

Not expected to be acutely toxic, but chips may mechanically cause adverse effects if ingested by waterfowl or aquatic life.

13. DISPOSAL CONSIDERATIONS

Disposal must be in accordance with applicable governmental regulations.

14. TRANSPORT INFORMATION

DEPARTMENT OF TRANSPORTATION (D.O.T.):

This product is not regulated by D.O.T. when shipped domestically by land.

CANADIAN TDG INFORMATION:

This product is not regulated by TDG when shipped domestically by land.



Date: 5/9/2012

MATERIAL SAFETY DATA SHEETS

15. REGULATORY INFORMATION

(Not meant to be all-inclusive – selected regulations represented)

Hazard Categories Under Criteria of SARA Title III Rules (40 CFR Part 370)

Immediate (Acute) Health	Ν	Delayed (Chronic) Health	Ν
Sudden Release of Pressure	Ν	Reactive	Ν
Fire		Ν	

The components of this product are all on the TSCA inventory list.

INGREDIENT RELATED REGULATORY INFORMATION:

RCLA RQ	SARA TPQ	
1000 I	LBS	N/A
1000 I	LBS	
N/A		
	1000 I 1000 I	1000 LBS 1000 LBS

SARA TITLE III, SECTION 313

This product does contain chemical(s), which are defined as toxic chemicals under and subject to the reporting requirements of, Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 986 and 40 CFR Part 372. See Section 2 Ethyl acrylate Methyl methacrylate Copper

CALIFORNIA PROP 65 – CARCINOGEN

This product does contain the following chemical(s), as indicated below, currently on the California list of Known Carcinogens. Ethyl acrylate Mercury

This product may contain trace levels of components known to the state of California to cause cancer:

Antimony (3+) Trioxide	Arsenic
Cadmium	Chromium (6+)
3.3'-Dichlorobenzidine	Formaldehyde
Lead	Nickel
Selenium Sulphide	

MASSACHUSETTS RIGHT TO KNOW

This product does contain the following chemicals(s), as indicated below, currently on the Massachusetts Right to Know Substance List.

Ethyl acrylate	Methyl methacrylate
Antimony (3+) Trioxide	Arsenic
Cadmium	Chromium (3+), (6+)
3.3'-Dichlorobenzidine	Formaldehyde
Lead	Nickel
Vinyl Acetate	

PENNSYLVANIA RIGHT TO KNOW

 This product does contain the following chemical(s), as indicated below, currently on the Pennsylvania Hazardous Substance List.

 Ethyl acrylate
 Methyl methacrylate

 Chromium (3+)
 Formaldehyde

NEWJERSEY RIGHT TO KNOW

This product does contain the following chemical(s), as indicated below, currently on the New Jersey Right-to-Know Substances List. Ethyl acrylate Methyl methacrylate

PENNSYLVANIA ENVIRONMENTAL HAZARD

This product does contain the following chemical(s), as indicated below, currently on the Pennsylvania Environmental Hazard List. Ethyl acrylate Methyl methacrylate

PENNSYLVANIA SPECIAL HAZARD

This product does contain the following chemical(s), as indicated below, currently on the Pennsylvania Special Hazard List. Ethyl acrylate



MATERIAL SAFETY DATA SHEETS

16. OTHER INFORMATION

NFPA HAZARD RATING (National Fire Protection Association):

	FIRE:
Fire	Must be preheated before ignition can occur.
1	HEALTH:
Health 0 0 Reactiv	<i>ity</i> Exposure under fire conditions would offer no hazard beyond that of ordinary
_	combustible materials.
Special	<u>REACTIVITY:</u>
	Normally stable, even under fire exposure conditions, and are not reactive with
	water.

REASON FOR ISSUE:

Innovative Plastics Inc. (IPI) believes that the information provided (including data and statements) are accurate as of the date hereof. No warranty, express or implied, is made concerning the information provided. Contact IPI for further information.



Date: 5/9/2012